

TECHNICAL REPORT



PRODUCT COMPARISON

As a result of research and testing, Centurion Products, Inc. has succeeded in reproducing the beauty and durability of natural stone in Centurion Stone. For your consideration, we provide this comparison of the construction requirements of Centurion Stone versus natural stone.

	CONSTRUCTION REQUIREMENTS	CENTURION STONE	NATURAL STONE
SAVINGS	FOOTINGS LINTELS WALL TIES RATE OF INSTALLATION DAILY INSTALLATION HEIGHT JOB SITE CLEANUP	NOT REQUIRED NOT REQUIRED NOT REQUIRED EXCELLENT UNLIMITED MINIMAL	REQUIRED REQUIRED REQUIRED POOR 3-4 FT DAILY CONSIDERABLE
PRODUCT INFORMATION	PACKAGING COVERAGE WEIGHT FREIGHT GRADE LINES COLOR RANGES SELECTION INTERIOR OR EXTERIOR	CARDBOARD CONTAINERS 10-14.6 SF PER BOX APPROX. 7.5 LBS/SF JUSTIFIABLE INSTALL TO GRADE STANDARD AND CUSTOM INTERIOR OR EXTERIOR	LOOSE VARYING PER TON 40-50 LBS/SF CONSIDERABLE INSTALLED BELOW GRADE TO FOOTING LEVEL LIMITED INTERIOR OR EXTERIOR WITH SUPPORTS
JOB REQUIREMENT	CEMENT PER 100 SF SAND PER 100 SF HANDLING EQUIPMENT/TOOLS	2 BAGS 800 LBS BY THE BOX STANDARD MASONRY TOOLS	7 TO 8 BAGS 2,800 LBS BY THE PIECE STONE HANDLING EQUIPMENT

Corporate Headquarters

50 Van Buren St.

Nashville, TN 37208

(615) 256-6694 Fax (615) 726-1795

Centurion® Products, Inc.

REPORT NO. CEN1024